




# DT2<sub>x</sub>

## Simple, Compact and Reliable Barcode Printers


The DT2<sub>x</sub> is perfect for printing retail labels and tags, hospital and recreation wristbands, plus other small, temporary labeling applications.



Ethernet, Serial and USB ports included



Uses direct thermal labels  
No ribbon required



Customized feeding mechanism for wristband media



Free labeling software GoLabel for easy printing

Barcodes Made Easy

## Desktop Printer

Model		DT2x
Print Method		Direct Thermal
Resolution		203 dpi (8 dot/mm)
Print Speed		7 IPS (177 mm/s)
Print Width		2.12" (54 mm)
Print Length		Min. 0.16" (4 mm)** ; Max. 68" (1727 mm)
Processor		32 bit RISC CPU
Memory	Flash	4 MB Flash (2 MB for user storage)
	SDRAM	16 MB
Sensor Type		Adjustable reflective sensor
Media	Types	Continuous form, black mark sensing, and punched hole; label length set by auto sensing or programming
	Width	Min. 0.6" (15 mm) – Max. 2.36" (60 mm)
	Thickness	Min. 0.003" (0.06 mm) – Max. 0.008" (0.20 mm)
	Label Roll Diameter	Max. 5" (127 mm)
Core Diameter		1" (25.4 mm), 1.5" (38.1 mm)
Printer Language		EZPL, GEPL, GZPL auto switch
Software	Label Design Software	GoLabel (for EZPL only)
	Driver	Windows 2000, XP, Vista, 7, 8 and Windows Server 2003&2008
	DLL	Windows 2000, XP and Vista
Resident Fonts	Bitmap Fonts	6, 8, 10, 12, 14, 18, 24, 30, 16x26 and OCR A&B Bitmap fonts 90°, 180°, 270° rotatable, single characters 90°, 180°, 270° rotatable Bitmap fonts 8 times expandable in horizontal and vertical directions
	Scalable Fonts	90°, 180°, 270° rotatable
Download Fonts	Bitmap Fonts	90°, 180°, 270° rotatable, single characters 90°, 180°, 270° rotatable
	Asian Fonts	90°, 180°, 270° rotatable and 8 times expandable in horizontal and vertical directions
	Scalable Fonts	90°, 180°, 270° rotatable
Barcodes	1-D Bar Codes	Code 39, Code 93, EAN 8/13 (add on 2 & 5), UPC A/E (add on 2 & 5), 1 2 of 5 & 1 2 of 5 with Shipping Bearer Bars, Codabar, Code 128 (subsets A, B, C), EAN 128, RPS 128, UCC 128, UCC/EAN-128 K-Mart, Random Weight, Post NET, ITF 14, China Postal Code, HIBC, MSI, Plessey, Telepen, FIM, GS1 DataBar, German Post Code, Planet 11 & 13 digit, Japanese Postnet, 12 of 5 with human readable check digit, Standard 2 of 5, Industrial 2 of 5, Logmars, Code 11, Code 49, Cadablock
	2-D Bar Codes	PDF417, Datamatrix code, MaxiCode, QR code, Micro PDF417, Micro QR code and Aztec code
Code Pages		Codepage 437, 850, 851, 852, 855, 857, 860, 861, 862, 863, 865, 866, 869 and 737 Windows 1250, 1251, 1252, 1253, 1254, 1255 and 1257 Unicode (UTF8, UTF16)
Graphics		Resident graphic file types are BMP and PCX, other graphic formats are downloadable from the software
Interfaces		USB 2.0 Serial port: RS-232 (DB-9) IEEE 802.3 10/100Base-Tx Ethernet port (RJ-45)
Control Panel		One Tri-color LED: Power (Green, Orange and Red) Function Key: FEED
Power		Auto Switching 100-240V AC, 50-60Hz
Real Time Clock		Standard
Environment	Operation Temperature	41°F to 104°F (5°C to 40°C)
	Storage Temperature	-4°F to 122°F (-20°C to 50°C)
Humidity	Operation	30-85%, non-condensing
	Storage	10-90%, non-condensing
Agency Approvals		CE(EMC), FCC Class A, CB, cUL and CCC
Dimension	Length	8.58" (218 mm)
	Height	6.77" (172 mm)
	Width	3.94" (100 mm)
Weight		2.65 lbs (1.2 Kg), excluding consumables
Options & Accessories		Cutter Module Label Dispenser External Label Roll Holder for 10" (250 mm) O.D. label rolls External Label Rewinder
* Specifications are subject to change without notice. All company and/or product names are trademarks and/or registered trademarks of their respective owners.		
** Minimum print height and maximum print speed specification compliance can be dependent on non-standard material variables such as label type, thickness, spacing, liner construction, etc. Godex is pleased to test non-standard materials for minimum print height and maximum print speed capability.		